



MEGA-PLUS

PRESSURE TANK

MegaPlus Pressure tank is an essential part of a pressurized water system that provides water pressure at a set level. The tank stores supplemental water between diaphragm and liner, and the pressurized air chamber is able to create a supply circle. This process reduces the number of times the motor need to start in order for the system pressure to remain at the set level.

The tension of diaphragm maintains water pressure within the system, ensuring proper operation of the dishwasher and washing machine, and robust flow for showering and bathing. MegaPlus provides high water pressure solution for the high rise building and the long distance pressure support. Insuring the water system works efficiently and energy saving with no maintenance.



EN ISO 9001



Lead-Free



NSF61

AQUASKY • SAFE • STABILİY



AQUASKY MEGAPLUG PRESSURE TANK

Model Number	Total Tank Volume		Accept Volume		Diameter		Height (Base Including)		Box Length		Box Width		Box Height		N.W.		G.W.		Shipping Volume
	Liter	Gal	Liter	Gal	cm	Inch	cm	Inch	cm	Inch	cm	Inch	cm	Inch	Kg	Lbs.	Kg	Lbs.	CUF
MEGA-8	8	2.0	3.5	0.92	20.3	8.0	30.4	12.0	21.3	8.4	21.3	8.4	32.4	12.8	2.1	4.6	2.5	5.5	0.52
MEGA-12	12	3.2	6.0	1.6	22.9	9.0	38.4	15.1	23.9	9.4	23.9	9.4	40.4	15.9	3.2	7.1	3.5	7.7	0.81
MEGA-18	18	4.5	9.5	2.5	28.0	11.0	36.4	14.3	29.0	11.4	29.0	11.4	38.5	15.2	3.7	8.2	4.1	9.0	1.14
MEGA-24	24	6.0	11.5	3.1	29.0	11.4	41.5	16.3	30.3	11.9	30.3	11.9	43.5	17.1	4.4	9.7	5.3	11.7	1.41
MEGA-40	40	10	20.0	5.3	29.0	11.4	65.3	25.7	30.3	11.9	30.3	11.9	67.3	26.5	6.6	14.6	7.5	16.5	2.18
Stand Models With Base																			
MEGA-60	60	14	42.8	11.3	39.0	15.3	59.2	23.4	40.0	15.7	40.0	15.7	61.5	24.2	10.8	23.8	12.1	26.7	3.47
MEGA-80	80	20	50.0	13.2	39.0	15.3	77.0	30.3	40.0	15.7	40.0	15.7	79.7	31.3	15.3	33.7	16.8	37.0	4.50
MEGA-100	100	28	58.5	15.5	39.0	15.3	96.3	37.9	40.0	15.7	40.0	15.7	98.3	38.7	19.9	43.9	21.7	47.8	5.55
MEGA-120	120	32	58.8	15.6	39.0	15.3	114.8	45.2	40.0	15.7	40.0	15.7	116.8	46.0	24.1	53.1	26.7	58.9	6.60
MEGA-130	130	34	85.6	22.6	55.0	21.7	77.9	30.7	56.0	22.1	56.0	22.1	76.0	29.9	24.0	52.9	27.0	59.5	8.84
MEGA-160	160	44	115	30.4	55.0	21.7	92.5	36.4	56.0	22.1	56.0	22.1	92.0	36.2	27.3	60.2	30.6	67.5	10.46
MEGA-200	200	53	128	33.8	55.0	21.7	106.0	41.7	56.0	22.1	56.0	22.1	108.0	42.5	32.8	72.3	36.1	79.6	12.01
MEGA-240	240	62	140	37.0	55.0	21.7	119.0	46.9	56.0	22.1	56.0	22.1	118.0	46.5	39.4	86.9	42.2	93.0	13.39
MEGA-300	300	81	167	44.1	55.0	21.7	145.7	57.4	56.0	22.1	56.0	22.1	147.0	57.9	48.2	106	54.2	119	16.37
MEGA-450	450	120	360	95.1	65.0	25.6	141.0	55.5	69.0	27.1	69.0	27.1	144.0	56.7	65.7	144	70.7	155	23.63

SHELL	SYSTEM CONNECTION	COATING	DIAPHRAGM
Cold Rolled Carbon Steel	304 Stainless Steel Connector	Triple Coated Liquid Paint	Heavy-Duty Butyl Rubber
LINER MATERIAL	FACTORY PRE-CHARGE	MAX WORKING TEMPERATURE	MAX WORKING PRESSURE
FDA Grade Polypropylene	4 Bar / 58 PSI	93°C / 200°F	16 Bar / 232 PSI



SHIELD COATING



N2 FILLING



AQUASKY PLUS

429 No. 36, Ln. 212, Sec 1, Hemu Rd.
Shengang Dist., Taichung City, Taiwan

TEL 886-4-2562-6368 FAX 886-4-2561-6332

WEB www.aquaskyplus.com

The shield coating is available for all models.